

Tekniske data luftisolert transformatorer, kapsling IP23:

Ytelse (kVA)	Type	Isol.klasse	Mål (mm)			Vekt (kg)	Fe-tap (Po) (W)	Cu-tap (Pk) (W)	ez (%)	er (%)	lc (xln)	Anb. forankoblet korts.l.vern (treg)	
			a (L)	b (B)	c (H)							230 V	400 V
4	3LT 4.00	F	377	350	461	45	90	168	4,2	4,2	24	16 A	13 A
6,3	3LT 6.30	F	427	400	515	63	128	246	4,1	3,9	21	20 A	13 A
10	3LT 10.0	F	427	400	515	66	168	294	3,4	2,9	19	32 A	20 A
16	3LT 16.0	F	481	450	590	122	269	386	2,8	2,4	17	50 A	32 A
20	3LT 20.0	F	481	450	590	148	280	371	2,2	1,9	20	63 A	32 A
25	3LT 25.0	F	599	550	630	170	387	496	2,6	2	15	80 A	40 A
30	3LT 30.0	F	599	550	630	212	494	472	2,1	1,6	16	80 A	50 A
40	3LT 40.0	F	670	540	827	200	130	1126	3,6	2,8	12	125 A	80 A
50	3LT 50.0	F	670	540	827	243	171	954	2,8	1,9	12	150 A	100 A
63	3LT 63.0	F	700	540	877	270	181	1254	3	2	12	200 A	125 A
80	3LT 80.0	F	700	540	877	323	237	1298	2,7	1,6	11	250 A	160 A
100	3LT 100	F	930	670	1057	370	251	1934	4,4	1,9	9	315 A	160 A
125	3LT 125	F	930	670	1057	430	356	2497	3,7	2	8	355 A	250 A
160	3LT 160	F	1050	740	1137	520	365	2912	3,9	1,8	7	500 A	315 A
200	3LT 200	F	1050	740	1137	613	456	3355	3,8	1,7	6	630 A	400 A
250	3LT 250	F	1210	860	1517	850	640	3797	4,2	1,5	12	800 A	500 A
315	3LT 315	F	1210	860	1517	950	651	5156	4,3	1,6	14	1000 A	630 A
400	3LT 400	F	1450	960	1557	1170	786	6681	6,1	1,7	8	1250 A	800 A
500	3LT 500	F	1450	960	1557	1310	935	7212	5,2	1,4	7	1600 A	1000 A

Målskisse:

